

FEATURES 設備特性

1. Integrated micro-processor control system.
微電腦整合控制系統。
2. Individual temperature control with digital controller for melting tank and dispensing nozzle.
全數位顯示功能—熔膠槽與噴槍獨立控溫、顯示。
3. Melting tank and dispensing nozzle could be heated orderly to avoid dispensing nozzle heating overtime and to reduce carbonization of hot melt adhesive (HMA).
熔膠槽與噴頭順序加熱—避免噴頭預熱時間過長，減少膠質碳化節省用電。
4. Weekly timer for setting the time to turn on and off machine automatically by requirements.
全週預約開關機功能—可依實際功能需求設定每天不同的開關機時間。
5. The function of keeping warm as a "Stand By" status to reduce carbonization of HMA and to conform to friendly environment.
停機保溫功能—減少膠質碳化符合環保節能需求。
6. Malfunction warning.
故障警報警示功能—確保安全，快速維修保養。
7. Constant flow by precision piston pump.
雙動氣壓泵浦一出膠穩定，使用壽命長。
8. Filters are installed inside manifold and dispensing nozzle, reducing maintenance and glue path block.
兩段式過濾裝置—減少管路阻塞，停工維修時間，有效提升生產效率。
9. 50% improvement on energy efficiency compared with traditional models.
節能省電—特殊結構設計，減少電能消耗，比傳統機型省電約 50%。
10. With plastic cover for low surface temperature, fine ability to keep-warmth, light weight, easier maintenance service.
塑化材質，表面溫度低、保溫效果佳、重量輕化、維修方便。



SPECIFICATIONS 設備規格

SPEC 規格	UNIT 單位	HP103P
Tank Capacity 膠槽容量	Liter	3
Max. Melting Rate 最大熔膠速率	Kg/HR	5
Max. Operation Temp. 最高操作溫度	°C	200
Max. Viscosity 最大使用黏度	CPS	8000
Sets of Gun 噴槍數量	Set	1
Max. Air Pressure 最大氣壓	Kg/cm ²	4
Dimensions (L x W x H) 尺寸(長 x 寬 x 高)	mm	514 x 507 x 485
Weight 重量	Kg	Approx. 25
Power Rate 功率	Watt	1300
Power Requirement 電力需求		220V AC, 5.9A, 50/60Hz, 1Φ

The flow rate depends on the viscosity of hot melt adhesive.
實際出膠量會依熱熔膠的黏稠度改變

HWANG SUN ENTERPRISE CO., LTD. 皇尚企業股份有限公司

ISO 9001:2008 SGS REGISTERED FIRM

Headquarters 臺灣總公司

No. 8, Keji 1st Rd.,
Annan District, Tainan 70955, Taiwan
70955 台南市安南區科技一路8號(科工區)
TEL: +886-6-3842889 FAX: +886-6-3842868

Machinery Division 機械事業中心

No.15, Hsin Ho 2nd Rd.,
Ann-Ping Industrial District, Tainan 70248, Taiwan
70248 台南市安平工業區新和二路15號
TEL: +886-6-2644191 FAX: +886-6-3842868

Taichung 台中營業所

4F-4, No. 82, Daying W. 1st St.,
Nantun District, Taichung 40865, Taiwan
40865 台中市南屯區大英西一街 82 號 4 樓之 4
TEL: +886-4-24739593 FAX: +886-4-24714414

Taipei 台北營業所

1F, No. 25-1, Hami St.,
Datong District, Taipei 10370, Taiwan
10370 台北市哈密街 25 之 1 號 1 樓
TEL: +886-2-25933744 FAX: +886-2-25923570

Suzhou 蘇州辦事處

Building No. 28, Li Tang Road, Kua Tang Town, Su Zhou
Industrial Park, Su Zhou City, Jiang Su Province, China
江蘇省蘇州市園區跨塘鎮蠡塘路逸苑別墅 28 棟
TEL: +86-512-67865516 FAX: +86-512-68557601

Dongguan Hwang Sun Industrial Co., Ltd.
東莞皇尚實業有限公司

Guangchang Road, Dingshan Village, Houjie Town, Dong-
guan, GuangDong, 523960, China
中國廣東省東莞市厚街鎮汀山村廣場路
TEL: +86-769-81636099 FAX: +86-769-81636399